


25X25X3 mm




- Housing: Plastic (UL 94V-0)
- Impeller: Plastic (UL 94V-0)
- Bearing: Hydraulic bearings
- Control Options: +/-FG/PWM
- Weight: 1.6 g

■ Air Flow-Static Pressure Characteristics




■ Dimensions Drawing (mm)



Model No.	Rated Voltage VDC	Operating Voltage Range VDC	Operating Temp. °C	Speed RPM	Input Current Amp	Input Power Watts	Maximum Air Flow		Maximum Air Pressure		Noise @30cm dB(A)
							CFM	l/min	Pa	mmH ₂ O	
① M1B2533H H40N10N0	3	2.5~3.5	-10~60	11000	0.250	0.750	0.50	14.05	70.3	7.17	26.7
② M1B2533H H40N20N0	3	2.5~3.5	-10~60	9600	0.160	0.480	0.43	12.26	53.6	5.46	23.9
③ M1B2533H H40N30N0	3	2.5~3.5	-10~60	7500	0.096	0.288	0.34	9.58	32.7	3.33	18.8
④ M1B2533H H40N40N0	3	2.5~3.5	-10~60	5200	0.045	0.135	0.23	6.64	15.7	1.60	11.2

■ 20% Duty Speed Sound Quality Spectrum



Notes: Specifications are subject to change without notice. Please refer to the product data sheet provided by our sales.

www.i-longwin.com

Suzhou Longwin High-Tech Co., LTD